

LC Series

DALI Dimming LED Driver


DALI调光LED恒流驱动器

Features:

- Dimmable with DALI signal
- Super slim design
- Driver for built-in use
- Push wire connections
- Three fixed selectable output currents
- For use in luminaires of protection class I
- Low ripple of output current for a higher quality of light
- high power factor
- Protections: opencircuit, shortcircuit, overload, overtemperature



- 适用DALI调光系统
- 超细长紧凑设计
- 内置式驱动
- 按压式接线端子
- 3组可选择电流输出
- 适用I类灯具
- 低电流纹波输出, 无频闪
- 高功率因数设计
- 输出开路, 短路, 过载和超温保护



Parameters:

Model No. 型号	Dimming Mode 调光方式	Input voltage 额定电压 (V)	Max. output 功率 (W)	Output current 输出电流 (mA)	Output voltage 输出电压 (V)	Power factor 功率因数 (λ)	THD 总谐波 (%)	Efficiency full load 效率 (%)	Ambient temperature 环境温度 ta (°C)	Max. casing temperature 最大外壳温度 tc (°C)	Isolation 隔离	Dimensions LxWxH 尺寸 (mm)	Weight 重量 (g)
LC-20-350/500/700D	DALI	220-240	20	350	2-60	0.95	<15	82	-20...+50	80	SELV	240x31x22	220
			20	500	2-40								
			20	700	2-30								
LC-40-350/500/700D	DALI	220-240	28	350	10-70	0.95	<15	85	-20...+50	80	SELV	280x31.5x22	230
			40	500	10-70			86					
			40	700	10-60			87					
LC-70-700D	DALI	220-240	1x70	700	40-100	0.95	<15	88	-20...+50	80	SELV	320x38x28	270
LC-70-1050D	DALI	220-240	1x70	1050	30-68	0.95	<15	87	-20...+50	80	SELV	320x38x28	270